



KRATOS
SAFETY
SOLUTIONS FOR LIFE

FIXED LINE SYSTEMS

2025 Catalogue



History

**2011**

Création de Kratos Safety dans un entrepôt de 650 m² à St Pierre de Chandieu (près de Lyon).

Founding of Kratos Safety in a 650 m² warehouse in St Pierre de Chandieu (close to Lyon).

Creación de Kratos Safety en un almacén de 650 m² en St Pierre de Chandieu (cerca de Lyon).

Fondazione di Kratos Safety in un'azienda di 650 m² a St Pierre de Chandieu (vicino a Lione).

Grundung des Unternehmens Kratos Safety in einem 650 m² großen Lagerhaus in St. Pierre de Chandieu (in der Nähe von Lyon).

 i-be safe
system**2015**

Kratos Safety lance I-Be Safe, logiciel facile et gratuit de calcul de tirant d'air.

Kratos Safety launches I-Be Safe, a free software that allows you to calculate easily your clearance for Kratos Safety fall arrest device.

Kratos Safety crea I-Be Safe, un software libre e fácil para calcular la distancia libre necesaria para el uso de los productos Kratos Safety.

Kratos Safety crea I-Be Safe, un software gratis e facile per calcolare el tirante d'aria dei prodotti Kratos Safety.

Kratos Safety bringt I-Be Safe auf den Markt, eine einfache und kostenlose Software zur Berechnung der Auffanghöhe.

**2017**

Kratos Safety emménage dans ses tout nouveaux locaux de 2000 m² à Heyrieux (proche de Lyon).

Kratos Safety moves in its new premises of 2000 m² in Heyrieux (close to Lyon).

Kratos Safety se muda a sus nuevas instalaciones de 2000 m² en Heyrieux (cerca de Lyon, en Francia).

Kratos Safety si trasferisce in un nuovissimo spazio di proprietà di 2000 m² a Heyrieux (nei pressi di Lione).

Kratos Safety zieht in seine brandneuen, 2000 m² großen Räumlichkeiten in Heyrieux (in der Nähe von Lyon) um.



2018

Lancement de:

- K-S.One, logiciel gratuit de gestion des EPI Kratos Safety,
- "Helixon", nouvelle gamme d'antichutes à rappel automatique et
- "KS-Line", gamme de ligne de vie horizontale.

Launching of K-S.One.

a free Kratos Safety PPE management software. As well as "Helixon", a new range of retractable fall arresters. But also "KS-Line", an horizontal Lifeline system.

Lanzamiento de:

- K-S.One, programa gratuito de gestión de EPI Kratos Safety,
- «Helixon», nueva gama de anticaídas retráctiles y
- «KS-Line», gama de líneas de vida horizontales.

Lancio di:

- K-S.One, software gratuito per la gestione dei DPI Kratos Safety,
- "Helixon", nuova gamma di anticaduta retrattili e
- "KS-Line", gamma di linee vita orizzontali.

Markteinführung von:

- K-S.One, kostenlose Software für das Management der PSA von Kratos Safety,
- „Helixon“, eine neue Produktpalette von Absturzsicherungen mit automatischer Rückführung und
- „KS-Line“, Sortiment an horizontalen Rettungsleinen.



2020

Extension de ses bâtiments de 1000 m² supplémentaires, ainsi qu'une nouvelle zone de formation de 300 m² permettant de se familiariser ou de peaufiner l'utilisation de l'ensemble de la gamme Kratos Safety.

Expansion of its premises with 1000 additional square meters, as well as a brand new 300m² training center to discover & perfect the usage of the entire Kratos Safety range.

Ampliación de sus edificios con 1000 m² adicionales, así como una nueva zona de formación de 300 m² para familiarizarse o perfeccionar el uso de toda la gama Kratos Safety.

Altri 1000 m² di spazio e una nuova area di 300 m² appositamente pensata in ottica formazione, per imparare a usare o perfezionare l'utilizzo di tutti i prodotti delle gamme Kratos Safety.

Gebäudeanbau von weiteren 1000 m² sowie ein neuer 300 m² großer Weiterbildungsbereich, um sich mit dem Einsatz der gesamten Produktpalette von Kratos Safety vertraut zu machen und diese besser zu nutzen.



2023

Segmentation des principales familles de produits en 3 gammes :

- PREMIUM
- MEDIUM
- ESSENTIAL

Segmentation of the main product families into 3 ranges :

- PREMIUM
- MEDIUM
- ESSENTIAL

Segmentación de las principales familias de productos en 3 gamas:

- PREMIUM
- MEDIUM
- ESSENTIAL


Segmentazione delle principali famiglie di prodotti in 3 gamme:

- PREMIUM
- MEDIUM
- ESSENTIAL

Segmentierung der wichtigsten produktfamilien in 3 Produktlinien :

- PREMIUM
- MEDIUM
- ESSENTIAL

Standards	Description	PPE Type 3* EPI Type 3*	Not PPE Type 3** Non EPI Type 3**
EN 353-1:2014 +A1:2017	Antichutes mobiles incluant un support d'assurage rigide Guided type fall arresters including a rigid anchor line Dispositivos anticaídas deslizantes sobre línea de anclaje rígida Anticaduta mobili con supporto di sicurezza rigido Mitlaufende Auffanggeräte einschließlich fester Führung	✓	
EN 353-2	Antichutes mobiles incluant un support d'assurage flexible Guided type fall arresters including a flexible anchor line Dispositivos anticaídas deslizantes sobre línea de anclaje flexible Anticaduta mobili con supporto di sicurezza flessibile Mitlaufendes Auffanggerät einschließlich beweglicher Führung	✓	
EN 795:2012 Type A	Dispositif d'ancrage nécessitant la fixation d'une ou plusieurs ancres structurelles Anchor device requiring the fixing of one or more structural anchors Dispositivo de anclaje que requiere la fijación de una o varias anclas estructurales Dispositivo di ancoraggio che richiede il fissaggio di uno o più ancoraggi strutturali Verankerungsvorrichtung, die die Befestigung eines oder mehrerer Strukturanker voraussetzt		✓
EN 795:2012 Type B	Dispositif d'ancrage ne nécessitant pas la fixation d'une ou plusieurs ancres structurelles Anchor device not requiring the fixing of one or more structural anchors Dispositivo de anclaje que no requiere la fijación de una o varias anclas estructurales Dispositivo di ancoraggio che non richiede il fissaggio di uno o più ancoraggi strutturali Verankerungsvorrichtung, die nicht die Befestigung eines oder mehrerer Strukturanker voraussetzt	✓	
EN 795:2012 Type C	Dispositif d'ancrage utilisant un support d'assurage flexible horizontal Anchor devices using a horizontal flexible anchor line Dispositivo de anclaje que usa una línea de anclaje flexible y horizontal Dispositivo di ancoraggio che sfrutta un supporto di sicurezza flessibile orizzontale Verankerungsvorrichtung mit biegsamem, horizontalem Absicherungsträger		✓
EN 795:2012 Type D	Dispositif d'ancrage utilisant un support d'assurage rigide horizontal Anchor devices using a horizontal rigid anchor line Dispositivo de anclaje que usa una línea de anclaje rígida y horizontal Dispositivo di ancoraggio che sfrutta un supporto di sicurezza rigido orizzontale Verankerungsvorrichtung mit starrem, horizontalem Absicherungsträger		✓
EN 795:2012 Type E	Dispositif d'ancrage à corps mort Deadweight anchoring device Dispositivo de anclaje de cuerpo muerto Dispositivo di ancoraggio a corpo morto Totkörper-Verankerungsvorrichtung	✓	
CEN/TS 16415:2013	Equipements de protection individuelle contre les chutes de hauteur - Dispositifs d'ancrage Recommendations pour les dispositifs d'ancrage utilisés simultanément par plus d'une personne Personal fall protection equipment - Anchor devices - Recommendations for anchor devices for use by more than one person simultaneously Equipos de protección individual contra caídas. Dispositivos de anclaje. Recomendaciones relativas a los dispositivos de anclaje para ser utilizados por varias personas al mismo tiempo Dispositivi individuali per la protezione contro le cadute - Dispositivi di ancoraggio - Raccomandazioni per dispositivi di ancoraggio per l'uso da parte di più persone contemporaneamente Persönliche Absturzschnutzausrüstung - Anschlagseinrichtungen - Empfehlungen für Anschlagseinrichtungen, die von mehreren Personen gleichzeitig benutzt werden		✓



DOLOMITICERT

Institute for the Certification of Personal Protective Equipment
S.C.A.R.L.
EU Notified Body n. 2008

Address: Villanova Zona Industriale, 7/A
32013 LONGARONE (BL) - ITALY
Tel.: +39 0437 573407 Fax: +39 0437 573131
Web site: www.dolomitcert.it E-mail: info@dolomitcert.it



COMPLIANCE OF CONFORMITY
number 151014



TABLE OF CONTENTS

Vertical Rail Systems (EN353-1)

KS 8000 (p. 45)
KS 9000 (p. 45)

Vertical Line Systems (EN353-1) (EN353-2)

KS 2001 (p. 38)
KS 6000 (p. 39)
KS 7000 (p. 39)


KS Rail Systems EN795 Type D

KS 5000 (p. 33)

KS Line System EN795 Type C

KS 4000 MAX-S (p. 6)
KS 4000 (p. 12)

Anchor Points EN795 Type A (p. 48)



INNOVATION



**35 m
span**

without intermediate

NEW

**KS 4000
MAX-S**

CONCRETE





I-BEAM

CE

EN 795 Type C
TS 16415 Type C

MAT.



SPAN

35 m for single span
30 m for multi-span




R (kN)

>28 kN

+





PLATINE D'EXTRÉMITÉ / EXTREMITY PLATE / PLACA DE EXTREMO /
PIASTRE DI ESTREMITÀ / ABSCHLUSSPLATTEN



REF.	FA 60 201 00
CE	EN 795 Type A, TS 16415 Type A EN 795 Type C ; TS 16415 Type C
MAT.	INOX 316
DIM.	H : 100 mm 172 x 36 mm
	2 x M12
MBS (kN)	45 kN
kg	0.68 KG

INTERMÉDIAIRE / INTERMEDIATE / INTERMEDIO / INTERMEDIO /
ZWISCHENPLATTEN




REF.	FA 60 204 00
CE	EN 795 Type C ; TS 16415 Type C
MAT.	INOX 316
DIM.	H : 120 mm 80 x 60 mm
SPAN	Maxi Every 35 m
	1 x M12
kg	0.57 KG
+	Reclining

ABSORBEUR D'ÉNERGIE / ENERGY ABSORBER / ABSORBEDOR DE ENERGÍA /
ASSORBITORE DI ENERGIA / FALLDÄMPFER



REF.	FA 60 202 02
CE	EN 795 Type C ; TS 16415 Type C
MAT.	INOX 316 / ALU
DIM.	461 x 141 mm
kg	4.25 KG

TENDEUR / TENSIONER / TENSOR / TENDITORE / SPANNER



REF.	FA 60 203 03
CE	EN 795 Type C ; TS 16415 Type C
MAT.	INOX 316
kg	1.45 KG
+	Tension indicator



CÂBLE / CABLE / CABLE / CAVO / SEIL



MARQUAGE / MARKING / MARCADO / MARCATURA / MARKIERUNG

689 chemin du Bucloy
Lieu-dit La Murière
38540 HEYRIEUX - FRANCE
Tel : +33 (0)4 72 48 78 27

	1 2 3 4 5 6 7			
☐ EN 795-A	☐ EN 353-1		Installed by	
☐ EN 795-C	☐ EN 353-2			
☐ EN 795-D	☐ EN TS 16415			
	☐ EN 353-2		System	
	☐ EN 355		☐ KS 4000	
	☐ EN 358		☐ KS 4000 MAX-S	
	☐ EN 360		☐ KS 5000	
Installation date		QR CODE	Inspection date	
2025 2026 2027 2028 2029 2030			2026 2027 2028 2029 2030 2031	
1 2 3 4 5 6 7 8 9 10 11 12				

REF.	FA 60 290 99
MAT.	
	1 X 19 Ø 8 mm
R (kN)	44 kN
	0.31 KG/m


REF.	FA 20 902 00
MAT.	
DIM.	100 x 80 mm

COULISSEAUX / CARRIAGE BODIES / CORREDERAS / CARRELLINI / LAÜFER



REF.	FA 60 206 01	FA 60 206 02	FA 70 023 01
	EN 795 Type B	EN 795 Type B	EN 12278
	x1	x1	x1
MAT.			
MBS (kN)	23 kN	25 kN	45 kN
	1.00 KG	0.21 KG	0.35 KG
+	Easy Overhead usage Pass Through	Pass Through	Easy Overhead usage

CONNECTEUR / CONNECTOR / CONNECTOR / CONNETTORE / VERBINDUNGSELEMENT



REF.	FA 50 305 16
	EN 362 Class B
	23 kN / 16.5 mm
MAT.	
	Triple Action
	0.21 KG
+	Individual Number



FA 60 203 03
(X2)



FA 60 201 00
(X2)

FA 20 902 00


READY TO USE KIT

FA 60 200 02 FOR UP TO 35 M


FA 60 202 02



689 chemin du Bac
Lieu-dit La Murière
38540 HEYRIEUX - FRANCE
Tel : +33 (0)4 72 48 78



- ☐ EN 795-A ☐ EN 353-1
- ☐ EN 795-C ☐ EN 353-2
- ☐ EN 795-D ☐ EN TS 16415



- ☐ EN 353-2
- ☐ EN 355
- ☐ EN 358
- ☐ EN 360



Installed by

- System
- ☐ KS 4000 ☐ KS 2001 ☐ KS 8000
- ☐ KS 4000 MAX-S ☐ KS 6000 ☐ KS 9000
- ☐ KS 5000 ☐ KS 7000

Installation date

2025	2026	2027	2028	2029	2030
1	2	3	4	5	6
7	8	9	10	11	12

QR CODE



Inspection date

2026	2027	2028	2029	2030	2031



FA 60 290 99
(35 M)



FA 60 204 00



FA 60 201 00
(X2)



FA 60 202 02

**READY TO
USE KIT**
**FA 60 200 03
FOR
UP TO 70 M**

FA 60 203 03
(X2)



FA 60 290 99
(70 M)

KRATOS SAFETY
689 chemin du Bucloy
Lieu-dit La Marrière
38540 HEYNEUX - FRANCE
Tel : +33 (0)4 72 48 78 27

1	2	3	4	5	6	7
---	---	---	---	---	---	---

☐ EN 795-A ☐ EN 353-1
☐ EN 795-C ☐ EN 353-2
☐ EN 795-D ☐ EN TS 16415

☐ EN 353-2
☐ EN 355
☐ EN 358
☐ EN 360


Installation date: 2026 2027 2028 2029 2030
5 6 7 8 9 10 11 12

QR CODE

Inspection date: 2026 2027 2028 2029 2030 2031

System:
☐ KS 4000 ☐ KS 2001 ☐ KS 801
☐ KS 4000 MAX-S ☐ KS 6000 ☐ KS 901
☐ KS 5000 ☐ KS 7000

Installed by:  



TRAPEZOIDAL ROOF





I-BEAM
WOODEN
BEAM



KS 4000

CONCRETE





SANDWICH PANEL ROOF

CE

EN 795 Type C
TS 16415 Type C

MAT.



SPAN


Maxi 15 m




R (kN)

>28 kN


+





MEMBRANE ROOF



STANDING SEAM ROOF



PLATINE D'EXTRÉMITÉ / EXTREMITY PLATE / PLACA DE EXTREMO /
PIASTRE DI ESTREMITÀ / ABSCHLUSSPLATTEN





REF.	FA 60 201 01
	EN 795 Type A; TS 16415 Type A EN 795 Type C; TS 16415 Type C
MAT.	 INOX 316
DIM.	H : 100 mm 172 x 39 mm
	2 x M12
MBS (kN)	30 kN
	0.53 KG

ABSORBEUR D'ÉNERGIE / ENERGY ABSORBER / ABSORBEDOR DE ENERGÍA /
ASSORBITORE DI ENERGIA / FALLDÄMPFER



REF.	FA 60 202 01
	EN 795 Type C ; TS 16415 Type C
MAT.	 INOX 316
DIM.	258 x 81 mm
	1.53 KG

INTERMÉDIAIRES / INTERMEDIATES / INTERMEDIOS / INTERMEDI / ZWISCHENPLATTE



REF.	FA 60 204 00	FA 60 204 01
	EN 795 Type C ; TS 16415 Type C	
MAT.	 INOX 316	
SPAN	Maxi every 15 m	
DIM.	H : 120 mm 80 x 60 mm	H : 75 mm 53 X 45 mm
	1 x M12	
	0.57 KG	0.25 KG
+	Reclining	---



TERMINAISON DE CABLE / CABLE TERMINATION / TERMINACIÓN DEL CABLE / TERMINAZIONE DEL CAVO / KABELABSCHLUSS



REF.	FA 60 205 00	FA 60 205 02	FA 60 205 03	FA 60 205 04
CE	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C
MAT.	INOX 316	INOX 316	ALU	INOX 316
Kg	0.50 KG	0.99 KG	0.13 KG	0.39 KG

TENDEURS / TENSIONERS / TENSOES / TENDITORI / SPANNER



REF.	FA 60 203 00	FA 60 203 02	FA 60 203 04
CE	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C
MAT.	INOX 316	INOX 316	INOX 316
Kg	1.00 KG	1.10 KG	1.13 KG
+	Tension indicator	Tension indicator	Tension indicator

CÂBLE / CABLE / CABLE / CAVO / SEIL

TERMINAISON USINE / FACTORY TERMINATION / TERMINACIÓN EN FÁBRICA / TERMINAZIONE IN FABBRICA / FABRIKTERMINIERUNG



REF.	FA 20 200 99
MAT.	
	7 x 19 Ø 8 mm
R (kN)	36 kN
	0.28 KG/m



REF.	FA 20 200 98
MAT.	
LG.	1 st m
R (kN)	36 kN
+	Compatible FA 20 200 99

INTERMÉDIAIRE / INTERMEDIATE / INTERMEDIO / INTERMEDIO / ZWISCHENPLATTEN

INSTALLATION AU SOL / FLOOR - MOUNTING / INSTALACIÓN EN EL SUELO / INSTALLAZIONE A TERRA / BODENMONTAGE

INSTALLATION EN INTERIEUR DE MUR / INTERNAL WALL MOUNTING / INSTALACIÓN INTERIOR DE PARED / INSTALLAZIONE INTERNO AL MURO / INSTALLATION INNENECKE WANDMONTAGE


INSTALLATION EN EXTERIEUR DE MUR / EXTERNAL WALL MOUNTING / INSTALACIÓN EXTERIOR DE PARED / INSTALLAZIONE ESTERNO AL MURO / INSTALLATION AUSSENECKE WANDMONTAGE



REF.	FA 60 216 90	FA 60 217 90	FA 60 218 90
	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C	EN 795 Type C ; TS 16415 Type C
MAT.			
	1 x M12	2 x M12	2 x M12
	0.81 KG	1.00 KG	1.00 KG




CAPUCHON DE CÂBLE / WIRE ROPE CAP
/ TAPA DE CABLE / TAPPO PER CAVO /
DRAHTSEILKAPPE




REF.	FA 20 200 97
MAT.	ALU

JONCTION DE CÂBLE / CABLE JOINT /
JUNTURA DEL CABLE / GIUNTO PER CAVI /
KABELVERBINDUNG



REF.	FA 60 200 97
MAT.	INOX
DIM.	L : 220 mm
	Only for 7x19 (FA 20 200 99)
R (kN)	36 kN
Kg	0.15 KG

MARQUAGE / MARKING / MARCADO /
MARCATURA / MARKIERUNG




REF.	FA 20 902 00
MAT.	ALU
DIM.	210 x 148 mm

COULISSEAUX / CARRIAGE BODIES / CORREDERAS / CARRELLINI / LAÜFER



REF.	FA 60 206 00	FA 60 206 01	FA 60 206 02	FA 70 023 01
CE	EN 795 Type B	EN 795 Type B	EN 795 Type B	EN 12278
Person icon	x1	x1	x1	x1
MAT.	INOX 316	INOX 316	INOX 316	INOX 316
MBS (kN)	23 kN	15 kN	25 kN	45 kN
Kg	0.64 KG	1.42 KG	0.21 KG	0.35 KG
+	Pass through	Easy Overhead usage, Pass through	Pass through	Easy Overhead usage

CONNECTEUR / CONNECTOR / CONNECTOR
/ CONNETTORE / VERBINDUNGSELEMENT




REF.	FA 50 305 16
CE	EN 362 Class B
Connector icon	23 kN / 16.5 mm
MAT.	INOX
Hand icon	Triple Action
Kg	0.21 KG
+	Individual Number

FA 90 203 00



FA 60 201 01
(X2)



FA 60 205 02



FA 60 202 01



FA 60 203 02



**READY TO
USE KIT**
**FA 60 200 00
FOR
UP TO 15 M**

FA 20 902 00

KRATOS SAFETY
SOLUTIONS FOR LIFE

889 chemin du Buisson
Lieu-dit La Marinière
38540 HEYRIEUX - FRANCE
Tel : +33 (0)4 72 48 78 27

1 2 3 4 5 6 7

☐ EN 795-A ☐ EN 353-1
☐ EN 795-C ☐ EN 353-2
☐ EN 795-D ☐ EN TS 16415

☐ EN 353-2
☐ EN 355
☐ EN 356
☐ EN 360

Installation date

2025	2026	2027	2028	2029	2030
3	4	5	6	7	8
9	10	11	12		

QR CODE


Inspection date

2026	2027	2028	2029	2030	2031

System

☐ KS 4000 ☐ KS 2001 ☐ KS 8000
☐ KS 4000 MAX-S ☐ KS 6000 ☐ KS 9000
☐ KS 5000 ☐ KS 7000

FA 20 200 98
+
FA 20 200 99
(15 M)






FA 90 203 00



FA 60 201 01
(X2)





FA 60 202 01



READY TO
USE KIT

FA 60 200 01
FOR
UP TO 30 M

FA 20 902 00



FA 60 203 02



FA 60 204 00






FA 60 205 02




FA 20 200 98
+
FA 20 200 99
(30 M)

I-BEAM


FIXATIONS / ANCHOR PLATES / PLACAS DE ANCLAJE / PIASTRE DI ANCORAGGIO / VERANKERUNGSPLETTEN



REF.	FA 60 207 01	FA 60 208 00	FA 60 208 01
MAT.			
DIM	208 x 208 mm	275 x 275 mm	208 x 208 mm
	LG : 80—150 mm Including 4 x M12 x 350 mm 2 x CSK M12 x 45 mm; 1 x CSK M12 x 30 mm	LG : 150—220 mm Including 4 x M12 x 60 mm 2 x CSK M12 x 45 mm; 1 x CSK M12 x 30 mm	LG : 80—150 mm Including 4 x M12 x 60 mm 2 x CSK M12 x 45 mm; 1 x CSK M12 x 30 mm
MBS (kN)	23 kN	26 kN	15 kN
	7.45 KG	10.0 KG	7.76 KG
Sys.	☒ KS 4000 ☒ KS 4000 MAX-S	☒ KS 4000 ☒ KS 4000 MAX-S	☒ KS 4000 ☐ KS 4000 MAX-S




REF.	FA 60 211 50E	FA 60 213 01	FA 60 201 02
MAT.			
DIM	H : 500 mm 224 x 224 mm	234 x 63 mm	H : 67 mm 146 X 40 mm
	LG : 80—150 mm Including 4 x M12 x 350 mm 1 x CSK M12 x 30 mm	LG : 80—150 mm Including 2 x M12 x 350 mm 1 x CSK M12 x 30 mm	Including 1 x M12
MBS (kN)	23 kN	15 kN	15 kN
	9.76 KG	2.63 KG	0.41 KG
+	---	For intermediate only	Energy absorption
Sys.		☒ KS 4000 ☐ KS 4000 MAX-S	



WOODEN BEAM

FIXATIONS / ANCHOR PLATES / PLACAS DE ANCLAJE / PIASTRE DI ANCORAGGIO / VERANKERUNGSPLETTEN



REF.	FA 60 207 00	FA 60 213 00
MAT.		
DIM	275 x 275 mm	312 x 100 mm
	LG : 150 —220 mm Including 4 x M12 x 350 mm 2 x CSK M12 x 45 mm; 1x CSK M12 x 30 mm	LG : 150 —220 mm Including 2 x M12 x 350 mm 1 x CSK M12 x 30 mm
MBS (kN)	26 kN	26 kN
	12.5 KG	3.90 KG
+	---	For intermediate only
Sys.	☒ KS 4000 ☐ KS 4000 MAX-S	



TRAPEZOIDAL ROOF

INTERFACE STANDARD / STANDARD INTERFACE / INTERFAZ ESTÁNDAR / INTERFACCIA STANDARD / STANDARDSCHNITTSTELLE




REF.	FA 60 226 00	FA 60 226 01	FA 60 226 01Z	FA 60 226 02
MAT.	 INOX 316	 INOX 316	 INOX 316	 INOX 316
Crown/Seam Distance	Min : 250 mm - Max : 350 mm			
DIM	H : 121 mm 368 x 288 mm	H : 141 mm 368 x 288 mm	H : 141 mm 368 x 288 mm	H : 141 mm 368 x 288 mm
	Including 10 x 8 mm rivets + 2 x M7 x 67 mm 2 flash tapes (50 x 280 mm)			
MBS (kN)	15 kN	15 kN	15 kN	15 kN
	2.18 KG	1.96 KG	2.13 KG	2.47 KG

Sys.

☒ KS 4000 ☐ KS 4000 MAX-S






TRAPEZOIDAL OR SANDWICH PANEL ROOF

POTELETS ABSORBANTS / CONSTANT FORCE POST / POSTES ABSORBENTES / PALETTI DI ASSORBIMENTO / ABSORBIERENDE




REF.	FA 60 227 00		FA 60 227 01		FA 60 227 02	
MAT.	 INOX 316 /  ALU		 INOX 316 /  ALU		 INOX 316 /  ALU	
Crown/Seam Distance	Mini : 200 - Max : 367 mm					
DIM	H : 194 mm 405 x 405 mm		H : 254 mm 405 x 405 mm		H : 254 mm 405 x 405 mm	
	Including 8 x 8 mm rivets + 4 flash tapes (50 x 125 mm)					
MBS (kN)	15 kN					
	3.74 KG		3.77 KG		4.37 KG	
Sys.	☒ KS 4000 ☐ KS 4000 MAX-S					






STANDING SEAM ROOF

INTERFACE STANDARD / STANDARD INTERFACE / INTERFAZ ESTÁNDAR / INTERFACCIA STANDARD / STANDARDSCHNITTSTELLE



REF.	FA 60 229 00	FA 60 229 01	FA 60 229 01Z	FA 60 229 02
MAT.				
Crown/Seam Distance	Min : 320 mm - Max : 650 mm			
DIM	H : 106 mm L : 700 mm	H : 126 mm L : 700 mm	H : 126 mm L : 700 mm	H : 126 mm L : 700 mm
	Including 2 standing seam clamps (for max 23 mm Bulb seam)			
MBS (kN)	15 kN	15 kN	15 kN	15 kN
	2.95 KG	2.70 KG	2.93 KG	3.26 KG
Sys.	☒ KS 4000 ☐ KS 4000 MAX-S			

REHAUSSE / EXTENSION / EXTENSIÓN / ESTENSIONE / ERHÖHEN



REF.	FA 60 229 90
MAT.	
DIM	50 x 150 mm
	0.73 KG
Sys.	☒ KS 4000 ☐ KS 4000 MAX-S



STANDING SEAM ROOF

POTELETS ABSORBANTS / CONSTANT FORCE POST / POSTE DE FUERZA CONSTANTE / PALO A FORZA COSTANTE / KONSTANTE KRAFTPOST



REF.	FA 60 228 00		FA 60 228 01	FA 60 228 02
MAT.				
Crown/Seam Distance	Min : 260 mm - Max : 500 mm			
DIM	H : 195 mm 550 x 360 mm		H : 255 mm 550 x 360 mm	H : 255 mm 550 x 360 mm
	Including 4 standing seam clamps (for max 23 mm Bulb seam)			
MBS (kN)	15 kN		15 kN	15 kN
	4.42 KG		4.45 KG	5.05 KG
Sys.	☒ KS 4000 ☐ KS 4000 MAX-S			




MEMBRANE ROOF

INTERFACE AVEC FIXATION À BASCULE / INTERFACE WITH SET OF 4 TOGGLES ANCHOR / INTERFAZ CON JUEGO DE 4 ANCLAJES DE PALANCA /
INTERFACCIA CON SET DI 4 ANCORE A GINOCCHIERA / SCHNITTSTELLE MIT EINEM SATZ VON 4 KNEBELANKERN




REF.	FA 60 230 00	FA 60 230 01	FA 60 230 01Z	FA 60 230 02
MAT.	 STEEL / INOX 316	 STEEL / INOX 316	 STEEL / INOX 316	 STEEL / INOX 316
DIM	H : 230 mm 327 x 327 mm	H : 240 mm 327 x 327 mm	H : 240 mm 327 x 327 mm	H : 240 mm 327 x 327 mm
	Including 4 Toggles	Including 4 Toggles	Including 4 Toggles	Including 4 Toggles
MBS (kN)	15 kN	15 kN	15 kN	15 kN
	3.65 KG	3.40 KG	3.97 KG	3.56 KG
Sys.	☒ KS 4000 ☐ KS 4000 MAX-S			



CONCRETE OR I-BEAM

POTELETS BÉTONS / CONCRETE POSTS / POSTES PARA HORMIGÓN / PALETTI PER CALCESTRUZZO / STANGEN FÜR BETON



REF.	FA 60 211 30 FA 60 211 50		FA 60 211 51	FA 60 201 02
MAT.				
DIM	H : 300 / 500 mm 275 mm x 275 mm		H : 515 mm 150 mm x 150 mm	H : 67 mm 146 X 40 mm
	4 x M12 Including 2 x CSK M12 x 45 mm ; 1 x CSK M12 x 25 mm		4 x M12 Including 1 x CSK M12 x 25 4 x M12	Including 1 x M12
MBS (kN)	26 kN		23 kN	15 kN
	10.23 KG 12.52 KG		3.96 KG	0.41 KG
Sys.	☐ KS 4000 ☒ KS 4000 MAX-S		☒ KS 4000 ☐ KS 4000 MAX-S	






I-BEAM



T-LINE SAFETY SYSTEM




CONCRETE

FA 60 039 12
FA 60 039 12S 
FA 60 039 24
FA 60 039 24S 



FA 60 039 12W
FA 60 039 12WS 
FA 60 039 24W
FA 60 039 24WS 



2X FA 60 039 01




REF.	FA 60 039 12	FA 60 039 12S	FA 60 039 24	FA 60 039 24S	FA 60 039 12W	FA 60 039 12WS	FA 60 039 24W	FA 60 039 24WS
------	--------------	---------------	--------------	---------------	---------------	----------------	---------------	----------------



PPE Regulation (EU) 2016/425 using
relevant § of EN 360 & EN 795

 MAX kg	140 KG							
---	--------	--	--	--	--	--	--	--

MAT. 	PA /  Ø4.5 mm	PA /  Ø4.8 mm	PA /  Ø4.5 mm	PA /  Ø4.8 mm	PA /  Ø4.5 mm	PA /  Ø4.8 mm	PA /  Ø4.5 mm	PA /  Ø4.8 mm
---	--	--	--	--	---	--	--	--

MAT. 								
---	--	--	--	--	--	--	--	--








R (kN) / MBS (kN)	12 kN / 17 kN							
-------------------	---------------	--	--	--	--	--	--	--

+	Reduced arrest distance Horizontal & vertical movement				Reduced arrest distance Horizontal & vertical movement Integrated rescue system			
---	---	--	--	--	---	--	--	--


 Kg	18.13 KG	19.53 KG	20.10 KG	21.50 KG
--	----------	----------	----------	----------



T-LINE SAFETY SYSTEM



OPTIMIZED CLEARANCE



I-BEAM OPTION

FA 60 039 02



REF.	FA 60 039 02
CE	EN 795 Type A
	x1
MAT.	STEEL
R (kN) / MBS (kN)	12 kN / 23 kN
	160 mm → 240 mm
+	For horizontal or vertical I-beams
Kg	4.35 KG



WALL MOUNTED INSTALLATION (WITH RECESS)



I-BEAM

KS 5000



FLOOR MOUNTED INSTALLATION





WALL MOUNTED INSTALLATION (FLUSH TYPE)

CE

EN 795 Type D
TS 16415 Type D

MAT.

ALU / INOX



R (kN)


28 kN

+



Zone 1

CONCRETE



CEILING MOUNTED INSTALLATION



RAIL / RAIL / RAÍL / BINARIO / ZWISCHENSCHIENE

MARQUAGE / MARKING / MARCADO / MARCATURA / MARKIERUNG



		689 chemin du Buisson Lieu-de-La-Mortière 38540 HEYRIEUX - FRANCE Tél : +33 (0)4 72 48 78 27																			
1 2 3 4 5 6 7 ☐ EN 795-A ☐ EN 353-1 ☐ EN 795-C ☐ EN 353-2 ☐ EN 795-D ☐ EN TS 16415	☐ EN 353-2 ☐ EN 355 ☐ EN 358 ☐ EN 360	0 m 0.5 1 1.5 2 2.5 3 3.5 4 4.5 5 5.5 6																			
Installed by 		System ☐ KS 4000 ☐ KS 2001 ☐ KS 8000 ☐ KS 4000 MAX-S ☐ KS 6000 ☐ KS 9000 ☐ KS 5000 ☐ KS 7000 ☐																			
Installation date <table border="1"> <tr> <td>2025</td><td>2026</td><td>2027</td><td>2028</td><td>2029</td><td>2030</td> </tr> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td> </tr> <tr> <td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td> </tr> </table>		2025	2026	2027	2028	2029	2030	1	2	3	4	5	6	7	8	9	10	11	12	QR CODE 	
2025	2026	2027	2028	2029	2030																
1	2	3	4	5	6																
7	8	9	10	11	12																
Inspection date <table border="1"> <tr> <td>2026</td><td>2027</td><td>2028</td><td>2029</td><td>2030</td><td>2031</td> </tr> <tr> <td></td><td></td><td></td><td></td><td></td><td></td> </tr> </table>		2026	2027	2028	2029	2030	2031														
2026	2027	2028	2029	2030	2031																

REF. FA 20 703 01

MAT.

LG. 3.0 m

4.10 KG

+ Extremity rail

Sys. KS 5000 ; KS 8000

FA 20 702 01

3.0 m

4.00 KG

KS 5000 ; KS 8000

REF.

FA 20 902 00

MAT.

DIM. 210 x 148 mm

RAIL INCURVÉ / CURVED RAIL / RAÍL INCURVADO / BINARIO INCURVATO / GEBOGENE SCHIENE



OUTER WALL
MOUNTING



INNER WALL
MOUNTING



FLOOR & CEILING
MOUNTING

REF. FA 60 503 00

MAT.

LG. 1.0 m

1.16 KG

FA 60 503 01

1.0 m

1.16 KG

FA 60 503 02

1.0 m

1.16 KG



FIXATIONS / CLAMPS / FIJACIONES / FISSAGGI / BEFESTIGUNGEN



Wall Mounted Installation
(with Recess)



Wall Mounted Installation
(Flush Type)



Floor / Ceiling Mounted Installation




REF.	FA 60 505 00	FA 60 504 00	FA 20 706 00	FA 20 706 02
MAT.	INOX 316	INOX 316	INOX 316	INOX
Kg	0.68 KG	0.30 KG	1.16 KG	0.90 KG

ACCESSOIRES / ACCESSORIES / ACCESORIOS / ACCESSORI / ZUBEHÖR

CHARIOTS / TROLLEYS / CORREDERAS / CARRELLI / LÄUFER



Wall Installation



Floor / Ceiling Installation

REF.	FA 20 704 00	FA 20 708 00	REF.	FA 60 500 00	FA 60 500 01
MAT.	ALU / INOX	INOX	MAT.	INOX 316 / Brass Wheels	INOX 316 / Brass Wheels
Kg	1.16 KG	0.08 KG	Kg	0.78 KG	0.60 KG
			R (kN)	15 kN	15 kN

COOL LINE

REF.


FA 60 033 18



CROSS LINE 1 MAXI 25 M

REF.


FA 60 007 02



CROSS LINE 2 MAXI 45 M

REF.

FA 60 007 04





ks 2001

ks 6000

ks 7000



KS 2001

CE

EN 353-2

MAT.



R (kN)

15 kN



REF. FA 20 200 00

MAT.



R (kN)

15 kN



100 KG



0.90 KG





KS 6000

CE

EN 353-1

MAT.



R (kN)

15 kN



REF. FA 20 200 02

MAT. INOX 316 & PES

R (kN) 15 kN

KG 100 KG

Kg 0.82 KG

OR

CE

EN 353-1,
PPE-R/11.119 (2 users)

MAT.



R (kN)

15 kN



REF. FA 20 200 04

MAT. INOX

R (kN) 15 kN

KG 140 KG

Kg 0.65 KG

+

Fall indicator

KS 7000

CE

EN 353-1

MAT.



R (kN)

15 kN

+



Zone 1



REF. FA 20 200 01

MAT. INOX 316

R (kN) 15 kN

KG 100 KG

Kg 0.60 KG

OR

CE

EN 353-1,
PPE-R/11.119 (2 users)

MAT.



R (kN)

15 kN



REF. FA 20 200 02


MAT. INOX 316 & PES

R (kN) 15 kN

KG 140 KG

Kg 0.82 KG


FIXATIONS HAUTES / HIGH ATTACHMENT POINTS / FIJACIONES ALTAS / FISSAGI ALTI / OBERE BEFESTIGUNGEN




REF.	FA 20 210 19
	EN 795 Type A
	x1
MAT.	
	4 x $\square$ $\varnothing$ M12
R (kN)	12 kN
	16.5 KG
Sys.	KS 2001 / KS 6000 / KS 7000




REF.	FA 20 209 00
	EN 795 Type A
	x1
MAT.	
	2 x $\square$ $\varnothing$ M12
R (kN)	15 kN
	1.30 KG
Sys.	KS 2001 / KS 6000 / KS 7000




REF.	FA 20 201 00
	EN 795 Type A
	x1
MAT.	
	2x M16 x 220 mm
R (kN)	15 kN
	3.26 KG
Sys.	KS 2001 / KS 6000 / KS 7000




REF.	FA 20 201 01
	EN 795 Type A
	x1
MAT.	
	2x M12 x 220 mm
R (kN)	15 kN
	1.25 KG
Sys.	KS 2001 / KS 6000 / KS 7000


FIXATIONS BASSES / END ATTACHMENT POINTS / FIJACIONES BAJAS / FISSAGGI INFERIORE / UNTEN BEFESTIGUNGEN


REF.	FA 20 201 01
CE	EN 795 Type A
	x1
MAT.	INOX 316
	2x M12 x 220 mm
R (kN)	15 kN
	1.25 KG
Sys.	KS 6000 / KS 7000



REF.	FA 20 203 00
MAT.	STEEL
	2 x $\square$ $\varnothing$ 8mm
	1.05 KG
Sys.	KS 2001

FIXATION INTERMÉDIAIRE / INTERMEDIATE ATTACHMENT / FIJACIÓN INTERMEDIARIA / FISSAGGIO INTERMEDIO / ZWISCHENBEFESTIGUNG
MARQUAGE / MARKING / MARCADO / MARCATURA / MARKIERUNG


REF.	FA 20 202 00
MAT.	INOX 316
	4 x M12
	0.49 KG
Sys.	KS 2001 / KS 6000 / KS 7000

		689 chemin du Becelay 33540 NETHOUX - FRANCE Tel : +33 (0)5 73 68 73 27	
1 2 3 4 5 6 7 ☐ EN 795-A ☐ EN 353-1 ☐ EN 795-C ☐ EN 353-2 ☐ EN 795-D ☐ EN TS 18415	8 m 1.5 1.0 0.5 0.1 0.05 0.01 0.005 0.001		
Installed by ☐ EN 353-2 ☐ EN 353 ☐ EN 355 ☐ EN 360		System ☐ KS 4000 ☐ KS 2001 ☐ KS 6000 ☐ KS 4000 MAX-3 ☐ KS 6000 ☐ KS 9000 ☐ KS 5000 ☐ KS 7000	
Installation date 2025 2026 2027 2028 2029 2030 1 2 3 4 5 6 7 8 9 10 11 12		OR CODE Inspection date 2026 2027 2028 2029 2030 2031	

REF.	FA 20 902 00
MAT.	ALU
DIM.	210 x 148 mm

SUPPORT D'ASSURAGE / LIFELINE / LÍNEA DE ANCLAJE / SUPPORTO DI SICUREZZA / SEILSICHERUNG



REF.	FA 20 207 00
	x1
MAT.	 INOX 316
R (kN)	34 kN
	0.39 KG
Sys.	KS 2001 / KS 4000 / KS 6000 / KS 7000



REF.	FA 20 200 99
	X1
MAT.	 INOX
	7 x 19 Ø 8 mm
R (kN)	36 kN
	0.28 KG/m
Sys.	KS 2001 / KS 4000 / KS 6000 / KS 7000




REF.	FA 20 200 98
MAT.	 INOX
LG.	1 st m
R (kN)	36 kN
+	Compatible FA 20 200 99

TENDEURS / TENSIONERS / TENSORES / TENDITORI / SPANNER



REF.	FA 20 204 00	FA 20 205 00	FA 20 205 01
	EN 353-2	EN 353-1	
MAT.	 STEEL	 INOX	
	6.0 KG	1.25 KG	1.10 KG
Sys.	KS 2001	KS 6000 / KS 7000	
+	---	For installations > 16 m	For installations < 16 m



REF.	FA 20 200 97
MAT.	ALU
Sys.	KS 2001 / KS 6000 / KS 7000



REF.	FA 20 206 00
MAT.	INOX
R (kN)	15 kN
 Kg	1.23 KG
Sys.	KS 7000





ks 8000

ks 9000



KS 8000

KS 9000



CE	EN 353-1
MAT.	ALU / STEEL / INOX
R (kN)	15 kN
+	Ex Zone 1



REF.	FA 20 700 00
MAT.	INOX
R (kN)	15 kN
KG	140 KG
KG	0.73 KG
+	Fall Indicator



EXTENSION HAUTE / TOP EXTENSION / EXTENSIÓN SUPERIOR
ESTENSIONE SUPERIORE / ERWEITERUNG OBEN




REF.	FA 20 701 00
LG.	1.5 m
MAT.	ALU
	2.90 KG
Sys.	KS 8000 / KS 9000




REF.	FA 20 701 01
	EN 795 Type A TS 16415 (4 Users)
LG.	Min : 110 mm - Max : 125 mm
MAT.	STEEL
	10.45 KG
Sys.	KS 8000 / KS 9000

RAIL / RAIL / RAÍL / ROTAIA / ZWISCHENSCHIENE

EXTRÉMITÉ BASSE / BOTTOM PART /
EXTREMO INFERIOR / ESTREMITÀ INFERIORE / UNTERES ENDE




REF.	FA 20 702 01
LG.	3.0 m
MAT.	ALU
	4.0 KG
Sys.	KS 5000 / KS 8000



REF.	FA 20 702 00
LG.	3.0 m
MAT.	ALU
	4.0 KG
Sys.	KS 9000




REF.	FA 20 703 01
LG.	3.0 m
MAT.	ALU
	4.10 KG
Sys.	KS 5000 / KS 8000



REF.	FA 20 703 00
LG.	3.0 m
MAT.	ALU
	4.10 KG
Sys.	KS 9000




FIXATIONS / CLAMPS / FIJACIONES / FISSAGGI / BEFESTIGUNGEN



REF.	FA 20 706 01	FA 20 706 00	FA 20 706 02	FA 20 705 00
	x1	x1	x1	x1
MAT.				
	M16	M16	M12	---
	4.08 KG	1.16 KG	0.90 KG	0.20 KG
Sys.	KS 9000 / KS 8000	KS 5000 / KS 9000	KS 5000 / KS 9000	KS 8000

REF.	FA 20 708 00
MAT.	
	0.08 KG
Sys.	KS 5000 / KS 9000

ACCESSOIRES / ACCESSORIES / ACCESORIOS / ACCESSORI / ZUBEHÖR




REF.	FA 20 704 00
MAT.	
	0.18 KG
Sys.	KS 5000 / KS 8000 / KS 9000

REF.	FA 20 707 00
MAT.	
	0.86 KG
Sys.	KS 9000

MARQUAGE / MARKING / MARCADO / MARCATURA / MARKIERUNG

		688 chemin de Buissey L'Écluse - La Motte 38540 HEYRIEUX - FRANCE Tel : +33 (0)4 72 48 79 27	
1 2 3 4 5 6 7 ☐ EN 795-A ☐ EN 353-1 ☐ EN 795-C ☐ EN 353-2 ☐ EN 795-D ☐ EN TS 16415	8 m 7.5 7 6.5 6 5.5 5 4.5 4 3.5 3 2.5 2 1.5 1 0.5 0	Installed by 	System ☐ KS 4000 ☐ KS 2001 ☐ KS 9000 ☐ KS 4000 MAX-X ☐ KS 4000 ☐ KS 9000 ☐ KS 5000 ☐ KS 7000
Installation date 2020 2021 2022 2023 2024 2025 1 2 3 4 5 6 7 8 9 10 11 12	QR CODE 	Inspection date 2020 2021 2022 2023 2024 2025 1 2 3 4 5 6 7 8 9 10 11 12	

REF.	FA 20 902 00
MAT.	
DIM.	210 x 148 mm



TRAPEZOIDAL ROOF




**WOODEN
BEAM**



SINGLE

CONCRETE





SANDWICH PANEL ROOF

ANCHOR POINTS




**STANDING
SEAM
ROOF**




I-BEAM





REF.	FA 60 038 00
CE	EN 795 Type A
	x1
MAT.	INOX / STEEL
DIM	---
R (kN) / MBS (kN)	12 kN / 23 kN
	CONCRETE Ø 20 mm x 150 mm
Kg	0.34 KG




REF.	FA 60 038 01
CE	---
	x1
MAT.	INOX
DIM	110 mm
R (kN) / MBS (kN)	12 kN / 23 kN
	CONCRETE Ø 20 mm x 150 mm
Kg	0.45 KG




REF.	FA 60 011 00
CE	EN 795 Type A
	x1
MAT.	INOX
DIM	H : 160 mm
R (kN) / MBS (kN)	12 kN / 23 kN
	M12 Ø13 mm X 115 mm
+	---
Kg	0.26 KG




REF.	FA 60 041 00
CE	EN 795 Type A
	x1
MAT.	STEEL
DIM	H : 450 mm 275 mm x 275 mm
R (kN) / MBS (kN)	12 kN / 15 kN
	4 x M12 (not included)
+	Compatible with all KRATOS SAFETY SRL from 6 m to 30 m, except KRONOS & TRITON
Kg	12.00 KG



REF.	FA 60 014 00	FA 60 014 01	FA 60 009 00
CE	EN 795 Type A, TS 16415 Type A		
	x4	x4	x3
MAT.	STEEL	STEEL	ALU
DIM	100 x 76 mm	100 x 76 mm	135 x 70 x 70 mm
R (kN) / MBS (kN)	15 kN / 23 kN	15 kN / 23 kN	14 kN / 23 kN
	M12 Ø13 mm X 10 mm	M12 (not included)	2 x M12 (not included)
	0.53 KG	0.37 KG	0.33 KG




REF.	FA 60 027 10	FA 60 027 12	FA 60 027 10A	FA 60 027 12A
CE	EN 795 Type A			
	x1		x1	
MAT.	INOX 316		STEEL	
DIM	57 x 45 x 32 mm		57 x 45 x 32 mm	
R (kN) / MBS (kN)	12 kN / 23 kN		12 kN / 23 kN	
	M10 (not included)	M12 (not included)	M10 (not included)	M12 (not included)
	0.06 KG	0.06 KG	0.06 KG	0.06 KG




REF.	FA 60 028 14
CE	EN 795 Type A
	x1
MAT.	INOX
DIM	165 x 44 x 67.5 mm
R (kN) / MBS (kN)	12 kN / 23 kN
	2 x M14 (not included) ---
	0.31 KG







REF.	FA 60 012 00
CE	EN 795 Type A
	x1
MAT.	STEEL
DIM	---
R (kN) / MBS (kN)	12 kN / 23 kN
	20 nails + 12 wood screws Min. 80 x 80 mm
	1.05 KG




REF.	FA 60 030 04
CE	EN 795 Type A
	x1
MAT.	INOX / STEEL
DIM	---
R (kN) / MBS (kN)	12 kN / 15 kN
	2 x M8 x 80 mm (not included) Ø 9 mm x 75 mm
	0.27 KG



REF.	FA 60 048 00
CE	EN 795 Type A
	x1
MAT.	INOX
DIM	H : 184.5 mm
R (kN) / MBS (kN)	12 kN / 15 kN
	Bolt on purlins Ø 30 mm
	0.76 KG



REF.	FA 60 048 01
CE	EN 795 Type A
	x1
MAT.	INOX
DIM	H : 272.5 mm
R (kN) / MBS (kN)	12 kN / 15 kN
	Bolt on purlins Ø 30 mm
	1.31 KG



REF.	FA 60 049 00
CE	EN 795 Type A, TS 16415 Type A
	x4
MAT.	INOX 316
DIM	H : 413 mm 400 mm x 200 mm
R (kN) / MBS (kN)	15 kN
	Toggle 36 mm hole on purlins
	2.10 KG



REF.	FA 60 300 01
CE	EN 795 Type A, TS 16415 Type A
	x4
MAT.	INOX
DIM	H : 304 mm 499 x 485 mm
R (kN) / MBS (kN)	15 kN / 15 kN
	Including 16 x 8 mm rivets and 4 flash tapes (50 x 125 mm)
+	---
Kg	10.56 KG




REF.	FA 60 041 01
CE	EN 795 Type A
	x1
MAT.	STEEL
DIM	H : 277.3 mm 499 mm x 485 mm
R (kN) / MBS (kN)	12 kN / 23 kN
	Including 16 x 8 mm rivets and 4 flash tapes (50 x 125 mm)
+	Compatible with all KRATOS SAFETY SRL from 6 m to 30 m, except KRONOS, TRITON & KALYPSO
Kg	14.28 KG



REF.	FA 60 042 01
CE	EN 795 Type A, TS 16415:2013 Type A
	x4
MAT.	INOX
Crown / Seam Distance	Min : 240 mm - Max : 350 mm
DIM	288 mm x 368 mm x 84 mm
R (kN) / MBS (kN)	15 kN / 15 kN
	Including 2 x M7 x 67 mm steel timber tek screws + 10 x 8 mm pop rivets and 2 flash tapes (50 x 200 mm)
+	Energy absorbing eye
Kg	2.1 KG






REF.	FA 60 034 00
CE	EN 795 Type A
	x1
MAT.	ALU
DIM	H : 100 mm 200 mm x 40 mm
R (kN) / MBS (kN)	12 kN / 15 kN
	Standing seam clamps (for max 23 mm Bulb seam)
Kg	0.83 KG



REF.	FA 60 310 01
CE	EN 795 Type A, TS 16415 Type A
	x4
MAT.	INOX
DIM	H : 301 mm 690 mm x 485 mm
R (kN) / MBS (kN)	15 kN / 15 kN
	Including 4 standing seam clamps (for max 23 mm Bulb seam)
Kg	10.41 KG



REF.	FA 60 041 02
CE	EN 795 Type A
	x1
MAT.	STEEL
DIM	H : 390 mm 456 mm x 250 mm
R (kN) / MBS (kN)	12 kN / 23 kN
	Including 4 standing seam clamps (for max 23 mm Bulb seam)
+	Compatible with all KRATOS SAFETY SRL from 6 m to 30 m, except KRONOS, TRITON & KALYPSO
Kg	12.70 KG





WALKWAY



EN 516:2006
CLASS 1



COMING SOON



INDEX

FA 20 200 00	38	FA 20 902 00 08 -14 - 34 - 41 - 47	FA 60 041 02	54
FA 20 200 01	39	FA 50 305 16 09 - 17	FA 60 042 00	53
FA 20 200 02	39	FA 60 007 02 36	FA 60 048 00	52
FA 20 200 04	39	FA 60 007 04 36	FA 60 048 01	52
FA 20 200 97	17 - 43	FA 60 009 00 51	FA 60 049 00	52
FA 20 200 98	16 - 42	FA 60 011 00 50	FA 60 200 00	18
FA 20 200 99	16 - 42	FA 60 012 00 52	FA 60 200 01	19
FA 20 201 00	40	FA 60 014 00 51	FA 60 200 02	10
FA 20 201 01	40 - 41	FA 60 014 01 51	FA 60 200 03	11
FA 20 202 00	41	FA 60 027 10 51	FA 60 200 97	17
FA 20 203 00	41	FA 60 027 10A 51	FA 60 201 00	8
FA 20 204 00	42	FA 60 027 12 51	FA 60 201 01	14
FA 20 205 00	42	FA 60 027 12A 51	FA 60 201 02	20 - 27
FA 20 205 01	42	FA 60 028 14 51	FA 60 202 01	14
FA 20 206 00	43	FA 60 030 04 52	FA 60 202 02	8
FA 20 207 00	42	FA 60 033 18 36	FA 60 203 00	15
FA 20 209 00	40	FA 60 033 19 36	FA 60 203 02	15
FA 20 210 19	40	FA 60 034 00 54	FA 60 203 03	8
FA 20 700 00	45	FA 60 038 00 50	FA 60 203 04	15
FA 20 701 00	46	FA 60 038 01 50	FA 60 204 00	08 - 14
FA 20 701 01	46	FA 60 039 01 30 - 31	FA 60 204 01	14
FA 20 702 00	46	FA 60 039 02 30	FA 60 205 00	15
FA 20 702 01	34 - 46	FA 60 039 12 30	FA 60 205 02	15
FA 20 703 00	46	FA 60 039 12S 30	FA 60 205 03	15
FA 20 703 01	34 - 46	FA 60 039 12W 31	FA 60 205 04	15
FA 20 704 00	35 - 47	FA 60 039 12WS 31	FA 60 205 98	15
FA 20 705 00	47	FA 60 039 24 30	FA 60 206 00	17
FA 20 706 00	35 - 47	FA 60 039 24S 31	FA 60 206 01	9 - 17
FA 20 706 01	47	FA 60 039 24W 31	FA 60 206 02	9 - 17
FA 20 706 02	35 - 47	FA 60 039 24WS 30	FA 60 206 03	9 - 17
FA 20 707 00	47	FA 60 041 00 50	FA 60 207 00	21
FA 20 708 00	35 - 47	FA 60 041 01 53	FA 60 207 01	20



INDEX

FA 60 208 00	20	FA 60 310 01	54
FA 60 208 01	20	FA 60 500 00	35
FA 60 211 30	27	FA 60 500 01	35
FA 60 211 50	27	FA 60 503 00	34
FA 60 211 50E	20	FA 60 503 01	34
FA 60 211 51	27	FA 60 503 02	34
FA 60 213 00	21	FA 60 504 00	35
FA 60 213 01	20	FA 60 505 00	35
FA 60 216 90	16	FA 70 023 01	9 - 17
FA 60 217 90	16		
FA 60 218 90	16		
FA 60 226 00	22		
FA 60 226 01	22		
FA 60 226 01Z	22		
FA 60 226 02	22		
FA 60 227 00	23		
FA 60 227 01	23		
FA 60 227 02	23		
FA 60 228 00	25		
FA 60 228 01	25		
FA 60 228 02	25		
FA 60 229 00	24		
FA 60 229 01	24		
FA 60 229 01Z	24		
FA 60 229 02	24		
FA 60 229 90	24		
FA 60 230 00	26		
FA 60 230 01	26		
FA 60 230 01Z	26		
FA 60 230 02	26		
FA 60 290 99	09 - 16		
FA 60 300 01	53		

**Looking for more fall arrest PPE ?
You can find them in our full catalogue.**



KRATOS SAFETY™ est une marque déposée. La société se réserve le droit de modifier les caractéristiques de ses produits sans préavis. Document non contractuel, sous réserve d'erreurs d'impression. Reproduction interdite.

KRATOS SAFETY™ is a registered trademark. The company reserves the right to change manufacturing specifications of its products without notice. Non-contractual document, subject to printing errors. Reproduction prohibited.

KRATOS SAFETY™ es una marca registrada. La empresa se reserva el derecho de modificar las características de sus productos sin previo aviso. Documento no contractual, bajo reserva de errores de impresión. Reproducción prohibida.

KRATOS SAFETY™ è un marchio registrato. La società si riserva il diritto di modificare, anche senza preavviso, le caratteristiche dei propri prodotti. Documento non contrattuale, con riserva di errori di stampa. È vietata la riproduzione.

KRATOS SAFETY™ ist eine eingetragene Marke. Das Unternehmen behält sich das Recht vor, die Merkmale seiner Produkte ohne Vorwarnung zu ändern. Vertraglich nicht bindendes Dokument, Druckfehler vorbehalten. Vervielfältigung verboten.



NOTES

A series of horizontal dotted lines for taking notes.



Acier
Steel
Acero
acciaio
Stahl



Aluminium
Aluminium
Aluminio
Alluminio
Aluminium




Acier inoxydable
Stainless steel
Acero inoxidable
Acciaio Inox
Rostfreier Stahl

PVC

PVC
PVC
PVC
PVC
PVC

PES

Polyester
Polyester
Poliéster
Poliestere
Polyester



Type de câble
Cable type
Tipo de cable
Tipo di cavo
Kabeltyp



360°

Rotation à 360°
360° rotation
Rotación de 360°
Rotazione a 360°
Rotation um 360°



I I2 G Exh IIC T6 Gb

Utilisable en Atmosphère Explosible
Usable in Explosive Atmosphere
Utilizable en atmósfera explosiva
Utilizzabile in atmosfera esplosiva
Verwendbar in explosionsgefährdeten Umgebungen



Conçu pour les panneaux solaires
Designed for Solar Panel
Diseñado para panel solar
Progettato per il pannello solare
Für Solarpaneele konzipiert




Vis incluses
Screw included
Tornillo incluido
Vite inclusa
Inklusive Schraube




Résistance à la rupture / Ouverture
Breaking strength / Gate opening
Resistencia a la ruptura / Apertura
Resistenza alla rottura / Apertura
Bruchfestigkeit / Öffnung



Type d'ouverture
Opening system
Tipo de apertura
Sistema di apertura
Öffnungssystem




Toit trapézoïdal
Trapezoidal roof
Tejado trapezoidal
Tetto trapezoidale
Trapez-blechdach



Toit en panneaux sandwich
Sandwich panel roof
Tejado de paneles sandwich
Tetto a pannelli sandwich
Sandwichplattendach




Toit à joint debout
Standing seam roof
Cubierta de junta alzada
Tetto ad aggraffatura verticale
Stehfalzdach




Membrane / toit TPO
Membrane / TPO roof
Techo de membrana / TPO
Tetto a membrana / TPO
Membran-/TPO-/FPO-Dach



Poutre IPN
I-Beam
Viga IPN
Trave IPN
I-Träger



Poutre en bois
Wooden beam
Viga de madera
Trave a legno
Holzbalken



Béton
Concrete
Hormigón
Calcestruzzo
Beton



Norme
Standard
Norma
Norma
Norm

MAT.

Matière
Material
Material
Material
Material

Span

Portée
Span
Lapso
Campata
Span

Crown /
Seam
Distance

Largeur d'ondes
Crown / Seam Distance
Ancho de onda
Larghezza d'onda
Wellenbreite

DIM.

Dimensions
Dimensions
Dimensiones
Dimensioni
Abmessungen



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer

R (KN) / MBS (KN)

+



Sys.

LG

Résistance statique (en kN) / Résistance à la rupture (kN)
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (kN)
Resistenza statica (in kN) / Resistenza alla rottura (kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (kN)

Point fort
Key feature
Ventaja principal
Punti forti
Produktvorteil

Poids du produit
Product weight
Peso del producto
Peso
Produktgewicht

Fixations à utiliser / Dimensions de la structure d'accueil
Fasteners to use / Dimensions of the receiving structure
Fijaciones que deben usarse / Dimensiones de la estructura receptora
Elementi di fissaggio da utilizzare / Dimensioni della struttura ospitante
Zu verwendende Befestigungen / Abmessungen der Aufnahmestruktur

Système compatible
Compatible system
Sistema compatibile
Sistema compatibile
Kompatibles System

Largeur Mini -> Maxi
Min -> Max width
Anchura Mínima -> Máxima
Larghezza Min -> Max
Breite Min. -> Max



S'utilise **uniquement** dans une direction horizontale (X)/verticale (Y) par rapport à l'installation
Can be used **only** in a horizontal (X)/vertical (Y) direction in relation to the installation
Se usa **únicamente** en una dirección horizontal (X)/vertical (Y) con respecto a la instalación
Può essere utilizzato **esclusivamente** seguendo una direzione orizzontale (X)/verticale (Y)
Im Verhältnis zur Installation nur in horizontaler (X)/vertikaler (Y) Richtung verwenden



S'utilise à la fois dans une direction horizontale et une direction verticale par rapport à l'installation
Can be used **both** in a horizontal and in a vertical direction in relation to the installation
Se usa **tanto** en una dirección horizontal como vertical con respecto a la instalación
Può essere utilizzato **sia** seguendo una direzione orizzontale che una verticale
Im Verhältnis zur Installation sowohl in vertikaler als auch in horizontaler Richtung verwendbar



S'utilise dans les 3 directions par rapport à l'installation
Can be used in the 3 directions in relation to the installation
Se usa en las 3 direcciones con respecto a la instalación
Può essere utilizzato in tutte e 3 le direzioni
Im Verhältnis zur Installation nur in alle 3 Richtungen verwendbar



KRATOS SAFETY SAS

689 Chemin du Buclay
38540 Heyrieux - FRANCE
Tel : +33 (0)4 72 48 78 27
Fax : +33 (0)4 72 48 58 32
E-mail: info@kratossafety.com

www.kratossafety.com



Printed on FSC® certified paper
from responsibly harvested sources

